

## Spec sheet

### Comfort Fit

The foot form ( "last" ) used to build these boots has been designed for the maximum comfort and accurate fit. A larger, naturally shaped steel toe cap is used to allow complete freedom of toe movement. The heel area is anatomically tapered to hold your heel snugly and comfortably in place, eliminating "the heel slip".



Warning: AirBoss-Defense's footwear is built to meet or exceed all applicable ANSI and CSA Grade 1 standards. Your work environment, tools and machinery may present special hazards that are difficult or impossible to protect against. In these cases, good judgement and safe working practices are essential to prevent injury. When working with dangerous tools or machinery, independent testing on all safety equipment, footwear and clothing is recommended.

Models	Patriot
	<b>Model: 9510S10, 9511S10</b>
<b>Outside Boot height:</b>	16"
<b>Midsole</b>	Duotex Midsole.
<b>Insulation</b>	Non insulated.
<b>Leg Lining</b>	Wool felt with calendared rubber coating.
<b>Toe Lining</b>	Net lining with calendared rubber coating.
<b>Tibia Protector</b>	Tibia protector, complete.
<b>Steel Toe Steel Plate</b>	Meets or exceeds standards listed below
<b>Steel Shank</b>	Double ridged steel.
<b>Outsole Pull on Loops</b>	Calendered with "Suretred" Design. For quick entry and easy taking.
<b>Sizes</b>	3 - 5F, 6 - 13H , 14 -15F
<b>Electrical Shock Resistance</b>	Meets or exceeds standards listed below.
<b>Standards</b>	NFPA - <u>1971-2000</u> Edition Standard for structural firefighting C.S.A. - Z195 - 92 protective footwear CSA Grade 1 Standards: Steel Toe - 93 ft/lb drop test Steel Plate - 300 ft/lb penetration test E.S.R. (EH) - 18 kv test