

117 LPG Water Heater

DECONTAMINATION ACCESSORIES

Capable of operating with existing trailer or shelter decontamination shower systems, the 117 LPG Water Heater will provide high-flow volume, tempered wash and rinse water to casualties.

The 117 LPG Water Heater will heat 4 gallons of water from 55 degrees F. to 95 degrees F. in one minute while maintaining a constant flow to a single shower suite.

Features

- Electronic pilot ignition driven by internal hydro-generator
- Copper heating coils for endless supply of hot water
- All water parts are solid copper or brass
- Quick-connect fittings for single water inlet and dual water outlets
- Safety flame sensor at burner pilot
- Automatic over-heating protection shut-off sensor
- Built-in corrosion resistant draft diverter
- Adjustable water flow restrictor to ensure that water flow demand will not exceed the heating capacity of the heater
- Portable, wheeled unit case constructed of stainless steel



Specifications

- Gas input: max. 117,000 BTU/hr.
- Water connection: 1/2" thread fitting NPT
- Exhaust vent diameter: 5"
- Net weight: 80 lbs.
- Dimensions: 22" x 39.5" x 13.25" (w x h x d)
- 1.8 GPM at 90 degree rise
- Minimum water flow: 1/2 gallon per min.
- Minimum water pressure: 18 Psi at 4 GPM
- Maximum water pressure: 150 Psi
- Requires propane fuel supply