



FIREPRO REMOTE CONTROL HYDRAULIC MONITOR

Model: FP3-750-RC-HYD

Specification:

Monitor

- ❖ 2.5" steel hydraulic monitor
- ❖ 750 gpm
- ❖ 3" or 4" flanged inlet
- ❖ 270° horizontal movement
- ❖ 105° vertical movement
- ❖ Red epoxy finish
- ❖ Heavy duty drive link hydraulic motors which incorporate a patented "Roller Stater[®]" motor design for increased efficiency and long life.

Hydraulic Power Unit

- ❖ HPU with an oil immersed pump-motor assembly for compact design.
- ❖ Single phase 110-115/220-230 VAC - 60Hz – 32/16 amps
- ❖ 1.75 HP with 1450 PSI (max.)
- ❖ Output flow 0.41 gpm to 3.9 gpm
- ❖ 0.75 gpm flow rate
- ❖ Ambient temp -4° F to 104° F
- ❖ Power unit can be mounted either vertically or horizontally.

Control Box

- ❖ Stainless steel enclosure
- ❖ 8 way joystick
- ❖ Power on light
- ❖ Power on/off switch
- ❖ 24 VAC for safety
- ❖ Optional water on/off switch
- ❖ Optional fog/stream switches