

AC-200 SET (PAIR), AUTO CRIB-IT Model AC-14

1. AUTOMATIC VEHICLE STABILIZATION DEVICE (QTY-2)

- 1.1 Automatic vehicle stabilizing device shall be provided for rapid vehicle stabilization and other cribbing operations.
- 1.2 Stabilizing device shall be spring-loaded and automatically rise to engage a vehicle's body or frame and lock into place.
- 1.3 Stabilizing device shall automatically adjust upward and lock during operations.
- 1.4 Stabilizing device shall allow positioning completely under vehicles.
- 1.5 Stabilizing device shall be capable of reaching a height of 13 inches.
- 1.6 Stabilizing device shall weigh less than 15 lbs.
- 1.7 Stabilizing device shall include a quick and easy ¼-turn lock.
- 1.8 Stabilizing device shall be compact when stowed.
- 1.9 Stabilizing device shall be made of metals and easily decontaminated.
- 1.10 Stabilizing device shall be rated for 2000 lbs maximum load.

AC-217 SET (PAIR), AUTO CRIB-IT Model AC-17

2. AUTOMATIC VEHICLE STABILIZATION DEVICE (QTY-2)

- 2.1 Automatic vehicle stabilizing device shall be provided for rapid vehicle stabilization and other cribbing operations.
- 2.2 Stabilizing device shall be spring-loaded and automatically rise to engage a vehicle's body or frame and lock into place.
- 2.3 Stabilizing device shall automatically adjust upward and lock during operations.
- 2.4 Stabilizing device shall allow positioning completely under vehicles.
- 2.5 Stabilizing device shall be capable of reaching a height of 17 inches.
- 2.6 Stabilizing device shall weigh less than 24 lbs.
- 2.7 Stabilizing device shall include a quick and easy ¼-turn lock.
- 2.8 Stabilizing device shall be compact when stowed.
- 2.9 Stabilizing device shall be made of metals and easily decontaminated.
- 2.10 Stabilizing device shall be rated for 2800 lbs maximum load.