

# PIPE

(GALVANIZED & ALUMINUM)

---

+ GALVANIZED	1
+ ALUMINUM	2

---





B-STYLE GALVANIZED PIPE SHOWN

**FOUR INCH GALVANIZED PIPE**

SIZE	PART NUMBER	WEIGHT
4" x 6'	220 P4-6	21.00 lbs
4" x 10'	220 P4-10	33.00 lbs
4" x 20'	220 P4-20	60.00 lbs

**SIX INCH GALVANIZED PIPE**

6" x 3'	220 P6-3	28.00 lbs
6" x 6'	220 P6-6	35.00 lbs
6" x 10'	220 P6-10	55.00 lbs
6" x 20'	220 P6-20	93.00 lbs

**EIGHT INCH GALVANIZED PIPE**

8" x 3'	220 P8-3	43.00 lbs
8" x 6'	220 P8-6	52.00 lbs
8" x 10'	220 P8-10	78.00 lbs
8" x 20'	220 P8-20	120.00 lbs

**TEN INCH GALVANIZED PIPE**

10" x 10'	221 P10-10	63.00 lbs
10" x 20'	221 P10-20	209.00 lbs

All 10" pipe has A-Style couplings.

**TWELVE INCH GALVANIZED PIPE**

12" x 10'	221 P12-10	173.00 lbs
12" x 20'	221 P12-20	278.00 lbs

All 12" pipe has A-Style couplings.  
12" Galvanized Locking Bar sold separately.

**GALVANIZED PIPE SPECS**

	I.D. (in)	WALL (in)	WALL (mm)	MAX (P.S.I.)	VACUUM
4"	4.25	0.059	1.5	175	30
6"	6.00	0.059	1.5	175	30
8"	8.00	0.059	1.5	175	30
10"	10.00	0.079	2.0	88	30
12"	12.00	0.079	2.0	88	30

Specifications to 1/8th of an inch // Specifications subject to change

PRICE AND DISCOUNT STRUCTURES SUBJECT TO CHANGE WITHOUT NOTICE.

NON-STOCK ITEM

SIZE

PART NUMBER

WEIGHT



B-STYLE ALUMINUM PIPE SHOWN

**THREE INCH ALUMINUM PIPE**

3" x 10'	720 PA3-10	15.00 lbs
3" x 20'	720 PA3-20	22.00 lbs
3" x 30'	720 PA3-30	29.00 lbs

Custom lengths available upon request.

**FOUR INCH ALUMINUM PIPE**

4" x 10'	720 PA4-10	24.00 lbs
4" x 20'	720 PA4-20	35.00 lbs
4" x 30'	720 PA4-30	46.00 lbs

Custom lengths available upon request.

**SIX INCH ALUMINUM PIPE**

6" x 10'	720 PA6-10	46.00 lbs
6" x 20'	720 PA6-20	64.00 lbs
6" x 30'	720 PA6-30	82.00 lbs

Custom lengths available upon request.

**EIGHT INCH ALUMINUM PIPE**

8" x 10'	720 PA8-10	68.00 lbs
8" x 20'	720 PA8-20	96.00 lbs

Custom lengths available upon request.

**ALUMINUM PIPE SPECS**

	FITTINGS	I.D. (in)	WALL (mm)	MAX (P.S.I.)	VACUUM
3"	Cast Aluminum	3.00	0.065	290	30
4"	Cast Aluminum	4.00	0.072	175	30
6"	Cast Aluminum	6.00	0.083	175	30
8"	Cast Aluminum	8.00	0.090	175	30

Specifications to 1/8th of an inch // Specifications subject to change

**TECH TIP**

Wil-loc's industrial-grade galvanized and aluminum pipe is fully vacuum rated. Vacuum ratings are dependent on the wall thickness of the pipe. For thinner walled pipe, vacuum relief valves should be used to prevent pipe from collapsing.

For easier coupling (especially of larger sizes) lubricate O-rings with Wil-lube (as seen in Specialty section). This will allow the ball to seat into the socket easier during first time usage.

PRICE AND DISCOUNT STRUCTURES SUBJECT TO CHANGE WITHOUT NOTICE.

WIL - 102108

© 2008 WIL-LOC

